



## HI-LITE INCLINED SCREENS

	Size of Screen	Mechanism Type 1 Deck	Weight (KG) 2 Deck	Power (KW) 3 Deck
3.0' x 6.0'	915mm x 1830mm	2/600/4.0	2/770/4.0	2/900/4.0
3.0' x 8.0'	915mm x 2440mm	2/700/4.0	2/800/4.0	2/1050/4.0
3.0' x 10.0'	915mm x 3050mm	2/800/4.0	2/900/4.0	2/1280/4.0
4.0' x 6.0'	1220mm x 1830mm	2/600/4.0	2/700/4.0	2/1100/4.0
4.0' x 8.0'	1220mm x 2440mm	2/700/4.0	2/900/4.0	2/1300/4.0
4.0' x 10.0'	1220mm x 3050mm	2/800/4.0	2/1100/4.0	2/1380/4.0
5.0' x 10.0'	1525mm x 3050mm	2/1000/4.0	2/1200/4.0	2/1450/4.0
5.0' x 12.0'	1525mm x 3660mm	2/1200/4.0	2/1800/4.0	2/2200/4.0

The 'HAWK' HiLite vibrating screen wholly manufactured in Melbourne Australia is simple and strong in construction and is made up of individual components which are bolted together with high tensile steel bolts. Each and every part can be replaced at the worksite without any special tools.

They can be used as light duty primary or finished product screens in single, double, or triple deck design with inclines from 15-30 degrees using single shaft centrifugal circular motion mechanisms running in large spherical bearings grease lubricated situated over the screen body.

Deck frames can be supplied to take various types of screening media either side tensioned, bolt down or modular systems.

Totally enclosed dust sealing arrangements are available.